

Timberwolf TW 230VTR

Working Range / Specification Sheet

FEATURES AND BENEFITS:

- Processing throughput of up to 5 tonnes/hr
- 24.8 hp Kubota diesel or 37 hp Briggs and Stratton petrol engine options
- Class-leading 230 mm x 160 mm infeed opening (6 ¼" cutting performance)
- Quad force rollers for ultimate grip, crushing & infeed power
- WolfTrack Dual Speed Tracking System (Low speed: 2.5 kph High speed: 5 kph)
- WolfTrack Variable Track System: 1300 mm maximum - 810 mm minimum width and 160 mm ground clearance
- Quick release infeed tray – no tools required
- Anti-vibration folding operator control platform
- Optional Bushy Hall Delta S3300 electric winch
- Integrated track recovery system
- Dual, ergonomic heavy duty infeed controls
- 280° adjustable discharge chute
- Patented exhaust cooler reduces exhaust temperatures up to 170°C*
- WolfPort blade access and removeable side panels for easy maintenance and servicing accessibility
- Double-sided reversible blades
- Timberwolf reliability and simplicity built-in
- 3-year warranty as standard with optional 5-year extended warranty

TW 230VTR PETROL SPECIFICATIONS	
PETROL ENGINE	
37 hp Briggs and Stratton (E10 compliant)	
Fuel tank capacity	36 litres
DIMENSIONS	
Weight	1172 kg
Height	2225 mm
Height with discharge tube removed	1365 mm
Length (tray down)	3460 mm
Length (tray up)	2725 mm
Width	810 mm - 1300 mm
CHIPPING FEATURES	
Feed method	Twin hydraulic rollers c/w Auto Feed Control
Maximum diameter infeed	160 mm (6 ¼")
Discharge tube	280° adjustable discharge
Blades	2 x 135 mm double sided, fully hardened



TO HIRE, GIVE US A CALL

01834 861540

Unit 1-4 Narberth Bridge Business Park, Narberth, Pembrokeshire, SA67 8RA

*Data sets made available from respective manufacturers official product information.