

Timberwolf TW 230HB

Working Range / Specification Sheet

FEATURES AND BENEFITS:

Lightweight, powerful, and reliable, the TW 230HB range is the best in class:

- Processing throughput of up to 5 tonnes/hr
- 24.8 hp Kubota diesel or 37 hp Briggs and Stratton petrol engine options
- Class-leading 230 mm x 160 mm infeed opening (6 ¼" cutting performance)
- Quad force rollers for ultimate grip, crushing & infeed power
- Sub 750 KG – Lightweight and manoeuvrable
- Dual, ergonomic heavy duty infeed controls
- 280° adjustable discharge chute
- Patented exhaust cooler reduces exhaust temperatures up to 170°C*
- WolfPort blade access and removeable side panels for easy maintenance and servicing accessibility
- Double-sided reversible blades
- Timberwolf reliability and simplicity built-in
- 3-year warranty as standard with optional 5-year extended warranty

TW 230HB SPECIFICATIONS	
PETROL ENGINE	
37 hp Briggs and Stratton (E10 compliant)	
Fuel tank capacity	18 litres
DIMENSIONS	
Weight	683 kg
Height	2213 mm
Height with discharge tube removed	1527 mm
Length (tray down)	3786 mm
Length (tray up)	3248 mm
Width	1520 mm
CHIPPING FEATURES	
Feed method	Twin hydraulic rollers c/w Auto Feed Control
Maximum diameter infeed	160 mm (6 ¼")
Discharge tube	280° adjustable discharge
Blades	2 x 135 mm double sided, fully hardened



TO HIRE, GIVE US A CALL

01834 861540

Unit 1-4 Narberth Bridge Business Park, Narberth, Pembrokeshire, SA67 8RA

*Data sets made available from respective manufacturers official product information.